

VARIABLE AT ANY HEIGHT

The hookable extension ladder 4946 – quick to deploy, comfortable operation, safe ascent and descent.

HOOKABLE EXTENSION LADDER

- Non-slip, ribbed, rolled profile rungs.
- Robust guide fittings made of steel.
- Secure attachment of the ladder thanks to preassembled, stable suspension hooks.
- · Space-saving storage when retracted.
- The variable angle of inclination allows some height compensation.

Features:

- · Press-fitted ladder feet.
- Ladder inner width 300 mm (top section).
- Angle of inclination between 65° and 75°.
- Hook size 30 mm.













Number of rungs	2×7	2×8	2×10
Stile top/bottom (approx. mm)	60/60	60/60	66/66
Number of rungs at max. extension	12	14	17
Length retracted (approx. m)	2.14	2.42	2.98
Length extended (approx. m)	3.54	4.10	4.94
Standing height (approx. m)	1.00 - 2.35	1.27 - 2.89	1.81 - 3.70
Reach height (approx. m)	3.00 - 4.35	3.27 - 4.89	3.81 - 5.70
Vertical height up to leaning point (approx. m)	2.04 - 3.38	2.31 - 3.92	3.12 - 4.73
Width extended top/bottom (approx. mm)	355/424	355/424	355/424
Weight (approx. kg)	7.8	8.2	10.8
Order no.	494614	494616	494620
Recommended sales prices without VAT €	229,00	255,00	299,00

Note: This ladder is not a leaning ladder as stipulated by EN 131-1 and may only be used when hooked in place.