

**NEW**



**H  
Y  
M  
E  
R**

# GRP LADDERS

Ladders made of glass fibre-reinforced plastic for special applications, such as in the chemical or pharmaceutical industry, as well as for working where electrical voltage is present.



# STEP LADDER WITH PLATFORM, SINGLE-SIDED ACCESSIBLE

EN  
131

- Ergonomic working on 88 mm step depth.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

## Features:

- Platform dimensions 250 x 250 mm.
- Approved for 1,000 V.
- According to EN 131.
- Legal warranty.



392605

	4	5	6
Number of steps incl. platform	4	5	6
Stile (approx. mm)	58	58	58
Length (approx. m)	1.66	1.91	2.16
Standing height (height to platform) (approx. m)	0.94	1.17	1.41
Reach height (approx. m)	2.94	3.17	3.41
Vertical height (approx. m)	1.56	1.79	2.03
Width top/bottom (approx. mm)	310/470	310/500	310/530
Base width (approx. m)	0.80	0.97	1.14
Weight (approx. kg)	7.9	9.4	11.4
Order no.	392604	392605	392606

# STEP LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

- Ergonomic working on 88 mm step depth.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

## Features:

- **Approved for 1,000 V.**
- **According to EN 131.**
- **Legal warranty.**



<b>Number of steps</b>	<b>2x3</b>	<b>2x4</b>	<b>2x5</b>
<b>Stile</b> (approx. mm)	58	58	58
<b>Length</b> (approx. m)	0.75	1.00	1.25
<b>Standing height</b> (approx. m)	0.25	0.48	0.72
<b>Reach height</b> (approx. m)	2.25	2.48	2.72
<b>Vertical height</b> (approx. m)	0.70	0.94	1.17
<b>Width</b> top/bottom (approx. mm)	350/450	350/470	350/500
<b>Base width</b> (approx. m)	0.63	0.80	0.97
<b>Weight</b> (approx. kg)	5.6	7.6	9.4
<b>Order no.</b>	<b>392406</b>	<b>392408</b>	<b>392410</b>

# RUNG LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- Equipped with comfort rungs from the third to the sixth rung from above.
- High-strength perlon straps provide reliable safety strut.

## Features:

- **Comfort rung depth of 52 mm.**
- **Approved for 1,000 V.**
- **According to EN 131.**
- **Legal warranty.**



392314

Number of rungs	2x6	2x7	2x8
Stile (approx. mm)	58	58	58
Length (approx. m)	1.83	2.11	2.39
Standing height (approx. m)	1.03	1.30	1.56
Reach height (approx. m)	3.03	3.30	3.56
Vertical height (approx. m)	1.71	1.98	2.24
Width top/bottom (approx. mm)	350/540	350/580	350/610
Base width (approx. m)	1.33	1.52	1.71
Weight (approx. kg)	10.1	11.6	13.2
Order no.	392312	392314	392316

# RUNG LEANING LADDER

EN  
131

- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.

## Features:

- **Approved for 1,000 V.**
- **According to EN 131.**
- **Legal warranty.**



Number of rungs	6	8	10
Stile (approx. mm)	58	58	58
Length (approx. m)	1.93	2.49	3.05
Standing height (approx. m)	0.81	1.35	1.89
Reach height (approx. m)	2.81	3.35	3.89
Width top/bottom (approx. mm)	410/410	410/410	410/810
Weight (approx. kg)	4.5	6.2	7.4
Ladder bottom	A	A	B
Order no.	391106	391108	391110

# hymer-access.com

**Hymer-Leichtmetallbau GmbH & Co. KG**

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

[ac.lg@hymer-alu.de](mailto:ac.lg@hymer-alu.de) | [hymer-access.com](https://hymer-access.com)