



**H  
Y  
M  
E  
R**

**HIGHER WITH  
SAFETY**

Our new products for safe  
and efficient work.

Recommended sales prices without VAT for commercial customers valid from 01.01.2024

---

# TABLE OF CONTENTS

## LADDERS AND STEPS

- 03 Step extension ladder, two-section
- 04 Hookable extension ladder
- 05 Step ladder with platform, single-sided accessible
- 06 Step ladder, double-sided accessible
- 07 Rung ladder, double-sided accessible
- 08 Rung leaning ladder
- 09 Step leaning ladder R13
- 10 Telescopic leaning ladder
- 11 Platform ladder HYMER PROTECT C
- 12 Platform ladder with long handrail
- 13 Platform ladder R13 with tip and roll wheels and long handrail
- 14 Machine step R13

## ACCESSORIES

- 15 Curved cross-beam for step extension ladder, two-section
- 15 Protection-KIT for roof ladders
- 15 Safety feet, height adjustable for telescopic leaning ladder



# STEP EXTENSION LADDER, TWO-SECTION

- Ergonomic working on 80 mm step depth on the upper section. Front step edges flush with stile.
- Lower weight due to the combination of steps and rungs.
- Increased slip resistance of steps and rungs thanks to a high rib extruded profile.
- Easier extension and retraction of the ladder thanks to steel guide fittings with plastic sliders.

## Features:

- Ladder inner width 300 mm (top section).
- Solid steel fittings.
- Press-fitted ladder feet.



EN  
131



Max.  
150 kg



**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY

Number of rungs/steps	2×8	2×10	2×12	2×14
Stile top/bottom (approx. mm)	83/66	83/66	83/71	83/83
Number of rungs/steps at max. extension	14	17	21	25
Length retracted (approx. m)	2.33	2.89	3.45	4.01
Length extended (approx. m)	4.01	4.85	5.97	7.09
Standing height (approx. m)	2.78	3.56	4.60	5.64
Reach height (approx. m)	4.78	5.56	6.60	7.64
Width extended top/bottom (approx. mm)	355/750	355/948	355/948	355/1,200
Weight (approx. kg)	11.2	13.7	16.7	19.3
Order no.	484616	484620	484624	484628
Recommended sales prices without VAT €	405.00	465.00	525.00	585.00



You don't want to compromise on work safety, but need more flexibility when using the ladder?

Use the curved cross-beam for increased ground clearance and more adaptability:

Order no. 0055628 for size 2×8+2×10, sales price without VAT € 93.00

Order no. 0055629 for size 2×12, sales price without VAT € 93.00

Order no. 0055630 for size 2×14, sales price without VAT € 93.00



# HOOKABLE EXTENSION LADDER

- Non-slip, ribbed, rolled profile rungs.
- Robust guide fittings made of steel.
- Secure attachment of the ladder thanks to preassembled, stable suspension hooks.
- Space-saving storage when retracted.
- The variable angle of inclination allows some height compensation.

## Features:

- **Press-fitted ladder feet.**
- **Ladder inner width 300 mm (top section).**
- **Angle of inclination between 65° and 75°.**
- **Hook size 30 mm.**



Max.  
150 kg



**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY

494620

Number of rungs	2×7	2×8	2×10
Stile top/bottom (approx. mm)	60/60	60/60	66/66
Number of rungs at max. extension	12	14	17
Length retracted (approx. m)	2.14	2.42	2.98
Length extended (approx. m)	3.54	4.10	4.94
Standing height (approx. m)	1.00 - 2.35	1.27 - 2.89	1.81 - 3.70
Reach height (approx. m)	3.00 - 4.35	3.27 - 4.89	3.81 - 5.70
Vertical height up to leaning point (approx. m)	2.04 - 3.38	2.31 - 3.92	3.12 - 4.73
Width extended top/bottom (approx. mm)	355/424	355/424	355/424
Weight (approx. kg)	7.8	8.2	10.8
Order no.	494614	494626	494620
Recommended sales prices without VAT €	229.00	255.00	299.00

Note: This ladder is not a leaning ladder as stipulated by EN 131-1 and may only be used when hooked in place.

# STEP LADDER WITH PLATFORM, SINGLE-SIDED ACCESSIBLE

EN  
131


Max.  
150 kg



- Ergonomic working on 88 mm step depth.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

## Features:

- Platform dimensions 250 x 250 mm.
- Approved for 1,000 V.
- Legal warranty.



392605

	4	5	6
Number of steps incl. platform	4	5	6
Stile (approx. mm)	58	58	58
Length (approx. m)	1.66	1.91	2.16
Standing height (height to platform) (approx. m)	0.94	1.17	1.41
Reach height (approx. m)	2.94	3.17	3.41
Vertical height (approx. m)	1.56	1.79	2.03
Width top/bottom (approx. mm)	310/470	310/500	310/530
Base width (approx. m)	0.80	0.97	1.14
Weight (approx. kg)	7.9	9.4	11.4
Order no.	392604	392605	392606
Recommended sales prices without VAT €	770.00	880.00	953.00

# STEP LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

Max.  
150 kg



- Ergonomic working on 88 mm step depth.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

## Features:

- Approved for 1,000 V.
- Legal warranty.



	2x3	2x4	2x5
Number of steps	2x3	2x4	2x5
Stile (approx. mm)	58	58	58
Length (approx. m)	0.75	1.00	1.25
Standing height (approx. m)	0.25	0.48	0.72
Reach height (approx. m)	2.25	2.48	2.72
Vertical height (approx. m)	0.70	0.94	1.17
Width top/bottom (approx. mm)	350/450	350/470	350/500
Base width (approx. m)	0.63	0.80	0.97
Weight (approx. kg)	5.6	7.6	9.4
Order no.	392406	392408	392410
Recommended sales prices without VAT €	605.00	655.00	745.00

# RUNG LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

Max.  
150 kg



- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- Equipped with comfort rungs from the third to the sixth rung from above.
- High-strength perlon straps provide reliable safety strut.

## Features:

- **Comfort rung depth of 52 mm.**
- **Approved for 1,000 V.**
- **Legal warranty.**



392314

Number of rungs	2x6	2x7	2x8
Stile (approx. mm)	58	58	58
Length (approx. m)	1.83	2.11	2.39
Standing height (approx. m)	1.03	1.30	1.56
Reach height (approx. m)	3.03	3.30	3.56
Vertical height (approx. m)	1.71	1.98	2.24
Width top/bottom (approx. mm)	350/540	350/580	350/610
Base width (approx. m)	1.33	1.52	1.71
Weight (approx. kg)	10.1	11.6	13.2
Order no.	392312	392314	392316
Recommended sales prices without VAT €	775.00	869.00	965.00

# RUNG LEANING LADDER

- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.

## Features:

- Approved for 1,000 V.
- Legal warranty.

EN  
131

Max.  
150 kg



	6	8	10
Number of rungs	6	8	10
Stile (approx. mm)	58	58	58
Length (approx. m)	1.93	2.49	3.05
Standing height (approx. m)	0.81	1.35	1.89
Reach height (approx. m)	2.81	3.35	3.89
Width top/bottom (approx. mm)	410/410	410/410	410/810
Weight (approx. kg)	4.5	6.2	7.4
Ladder bottom	A	A	B
Order no.	391106	391108	391110
Recommended sales prices without VAT €	385.00	475.00	539.00



# STEP LEANING LADDER R13

- Work safety in the highest slip resistance class R13.  
Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth.  
Front step edges flush with stile.
- Very robust thanks to torsion-resistant,  
swaged stile/step connection.
- More ground clearance and stability thanks  
to the curved cross-beam.
- Convenient, ergonomic ladder width.

## Features:

- R13 coating on the entire step surface.
- Inner ladder width 370 mm.

EN  
131




Max.  
150 kg



**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY



Number of steps	8	10	12	14	16
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	2.22	2.72	3.22	3.72	4.22
Standing height (approx. m)	1.17	1.63	2.09	2.56	3.02
Reach height (approx. m)	3.17	3.63	4.09	4.56	5.02
Width top/bottom (approx. mm)	425/425	425/425	425/961	425/961	425/961
Weight (approx. kg)	5.8	7.2	9.7	10.7	12.1
Ladder bottom	A	A	B	B	B
Order no.	891208	891210	891212	891214	891216
Recommended sales prices without VAT €	299.00	369.00	459.00	549.00	599.00

8014

# TELESCOPIC LEANING LADDER

EN  
131

Max.  
150 kg

- Ergonomic working on 80 mm step depth.
- Rubber pads protect susceptible surfaces and reduce the risk of slipping.
- Highly stable thanks to foldable, transport-optimised telescopic stabilisers.
- Central unlocking with just one grip.
- Requires little space to transport and store.
- Smooth, safe extension and retraction.
- Convenient, ergonomic ladder width.
- Anodised stiles prevent dirty hands from aluminium abrasion.

## Features:

- **Legal warranty.**



<b>Number of steps</b>	<b>11</b>	<b>13</b>
<b>Length</b> retracted (approx. m)	0.87	0.93
<b>Length</b> extended (approx. m)	3.49	4.09
<b>Standing height</b> (approx. m)	2.49	3.09
<b>Reach height</b> (approx. m)	4.49	5.09
<b>Width</b> top/bottom (approx. mm)	440/550	440/560
<b>Weight</b> (approx. kg)	15.2	17.4
<b>Order no.</b>	<b>801411</b>	<b>801413</b>
<b>Recommended sales prices without VAT €</b>	<b>695.00</b>	<b>799.00</b>

# PLATFORM LADDER HYMER PROTECT C

- Hands-free, safe working thanks to fall protection on all sides.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Comfortable way up thanks to 80 mm step depth.
- Highly stable thanks to foldable, transport-optimised stabilisers.
- Optimum transport by means of tip and roll wheels.
- Brace-free support section for more flexible usage.

## Features:

- Platform dimensions 500 x 424 mm.



EN  
131-7

NF P 93-  
352/353



Max.  
150 kg  
↓

10  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY

	2	3	4	5	6
Number of steps incl. platform	2	3	4	5	6
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	1.61	1.86	2.11	2.36	2.61
Standing height (height to platform) (approx. m)	0.46	0.69	0.92	1.16	1.39
Reach height (approx. m)	2.46	2.69	2.92	3.16	3.39
Vertical height (approx. m)	1.51	1.74	1.97	2.21	2.44
Width (approx. mm)	572	1,168	1,168	1,730	1,730
Base width (approx. m)	0.81	1.04	1.20	1.36	1.51
Folded L×W×H (approx. m)	1.75×0.58×0.28	2.00×0.61×0.32	2.26×0.61×0.32	2.51×0.61×0.32	2.76×0.61×0.32
Weight (approx. kg)	11.1	15.3	15.8	18.2	19.3
Foldable stabilisers	-	✓	✓	✓	✓
Order no.	838302	838303	838304	838305	838306
Recommended sales prices without VAT €	570.00	660.00	720.00	780.00	840.00

# PLATFORM LADDER WITH LONG HANDRAIL

- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Ergonomic working on 80 mm step depth. Front step edges flush with stile.
- Detachable, rigid brace prevents accidental folding.
- Ergonomically shaped handrails on both sides.
- Conical design ensures ladder stability.

## Features:

- Platform dimensions 440 x 400 mm.
- Guardrail height above platform 1,000 mm.



EN  
131



Max.  
150 kg



**10**  
YEAR  
GUARANTEE



Number of steps incl. platform	4	5	6	8	10
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	2.10	2.35	2.60	3.10	3.60
Standing height (height to platform) (approx. m)	0.95	1.18	1.42	1.88	2.34
Reach height (approx. m)	2.95	3.18	3.42	3.88	4.34
Vertical height (approx. m)	1.97	2.20	2.43	2.89	3.36
Width (approx. mm)	653	677	700	747	793
Base width (approx. m)	0.99	1.15	1.30	1.62	1.94
Weight (approx. kg)	10.3	11.5	12.5	15.7	19.0
Order no.	807804	807805	807806	807808	807810
Recommended sales prices without VAT €	425.00	465.00	509.00	569.00	639.00

# PLATFORM LADDER R13 WITH TIP AND ROLL WHEELS AND LONG HANDRAIL

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth. Front step edges flush with stile.
- Solid aluminium storage tray with bucket hook.
- High-strength perlon straps provide reliable safety strut.
- Detachable, rigid braces prevent accidental folding.
- Ergonomically shaped handrails on both sides.
- Conical design ensures ladder stability.

## Features:

- R13 coating on the entire step surface.
- Platform dimensions 440 x 400 mm.
- Guardrail height above platform 800 mm.



EN  
131



Max.  
150 kg



10  
YEAR  
GUARANTEE



Number of steps incl. platform	4	5	6	7	8	9	10	12
Stile (approx. mm)	71	71	71	71	71	71	71	71
Length (approx. m)	1.95	2.20	2.45	2.70	2.95	3.20	3.45	3.95
Standing height (height to platform) (approx. m)	0.95	1.18	1.42	1.65	1.88	2.11	2.34	2.80
Reach height (approx. m)	2.95	3.18	3.42	3.65	3.88	4.11	4.34	4.80
Vertical height (approx. m)	1.77	2.00	2.24	2.47	2.70	2.93	3.16	3.62
Width (approx. mm)	653	677	700	723	747	770	793	840
Base width (approx. m)	0.99	1.15	1.30	1.46	1.62	1.78	1.94	2.26
Weight (approx. kg)	11.7	12.9	14.2	16.2	17.6	18.5	19.8	24.5
Safety strut (perlon straps)	-	-	-	-	✓	✓	✓	✓
Order no.	868104	868105	868106	868107	868108	868109	868110	868112
Recommended sales prices without VAT €	759.00	799.00	849.00	899.00	949.00	999.00	1,099.00	1,249.00



# MACHINE STEP R13

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Non-slip, convenient ascent thanks to the large step.
- Extremely high stability for heavy-duty use.
- Lightweight for ergonomic positioning.

## Features:

- Aluminium perforated plate R13.
- Platform dimensions 580 x 350 mm.

EN  
14183



Max.  
150 kg



**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY



Number of steps incl. platform	1	2	3	4	5
Standing height (approx. m)	0.20	0.40	0.60	0.80	1.00
Reach height (approx. m)	2.20	2.40	2.60	2.80	3.00
Overhang (approx. m)	0.38	0.63	0.87	1.10	1.34
Width (approx. mm)	600	680	700	730	760
Weight (approx. kg)	2.8	5.6	7.9	10.4	14.6
Order no.	6878164	6878264	6878364	6878464	6878564
Recommended sales prices without VAT €	249.00	489.00	649.00	829.00	999.00

# ACCESSORIES



## Curved cross-beam for step extension ladder, two-section

- For increased ground clearance and more adaptability.
- Self assembly by using tools.
- Including fastening material.

For type	4846		
For number of rungs/steps	2x8+2x10	2x12	2x14
Length (approx. mm)	876	1,056	1,075
Weight (approx. kg)	1,2	1,4	1,4
Order no.	0055628	0055629	0055630
Price/piece without VAT €	93.00	93.00	93.00



## Protection-KIT for roof ladders

- To protect the roofing and ladder.
- Content: 2 adhesive strips.

For type	4092+4093+4095+4096		
Dim. LxWxH (approx. mm)	1,950x20x3		
Material	rubber (EPDM)		
Weight (approx. kg)	0.2		
Order no.	0055610		
Price/set without VAT €	19.90		



## Safety feet, height adjustable for telescopic leaning ladder

- Approved for 150 kg, according to EN 131.
- Max. adjustable up to 220 mm.
- Self assembly by using tools.
- Incl. extension kit for the folding stabiliser.

For type	8014		
Weight (approx. kg)	2,5		
Order no.	0055529		
Price/set without VAT €	169.00		



# Hymer-Leichtmetallbau GmbH & Co. KG

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

international-sales@hymer-alu.de | [hymer-access.com](https://hymer-access.com)

## hymer-access.com

You can also download all  
brochures from our website:



Written information on the products and images thereof may differ from the actual design in individual cases.  
Errors, price changes and design modifications are also reserved.

Version: 01/2024